

T Series

Sunlite 01957-SU Incandescent T6.5 Tubular Light Bulb, BA15D Double Contact Bayonet Base 25 Watts, 170 Lumens, Dimmable, Mercury Free, 2600K Warm White, 1 Count, Clear

T6.5 Tubular

DESCRIPTION:

Sunlite T6.5 25 watt incandescent tubular bulbs are suitable for use in many applications. Wall light fixtures, decorative lighting, crystal chandelier and more. These fully dimmable bulbs contain no mercury or other harmful chemicals. They feature a double contact bayonet base (BA15D) and put out a warm white light. 1500 hour life span. Great for bedrooms, kitchens, dining rooms, living areas, offices, showrooms, landscape lighting, signs, and more. Commercial and residential use

FEATURES:

- DC BAYONET BASE With their double contact bayonet base (BA15D) these clear tubular bulbs are suitable for use in many applications. Wall light fixtures, decorative lighting, crystal chandelier and more
- WARM WHITE LIGHT These 25 watt traditional incandescent bulbs put out a comfortable warm white light at 2600K. 120 volts output.
- DIMMABLE Adjust the light to suit your mood. When attached to a dimmer switch the 170 lumen output of these lamps can be adjusted from 100% to 1% and anywhere in between with no flickering
- 2,000 HOUR LIFE SPAN With a long 2000 hour life span you'll need to replace hard to reach bulbs less often
- MERCURY FREE These bulbs contain no mercury or other harmful chemicals making them safe for the environment. Bulb measures 5.5 inches high, 0.75 inches in diameter





SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours Finish

Average Life Span Years

Electrical Characteristics

Watts Volts

Light Characteristics

Lumens Brightness Emitted Color

Additional Features

Title 20

Base

T6.5 DC 2000 Clear Double Contact Bayonet (BA15d)

25 120

170 Warm White

Lawful for sale in California

Product Dimensions

MOL (in)
Diameter (in)
Item Dimension (in)
Package Dimension (in)
Package Weight (lb)

Product Data

Case Unit Rate Pack Size Item UPC Package Type 5.25 .80

(W) 0.79 (H) 5.7 (D) 0.79 (W) 1 (H) 8.2 (D) 2.8

0.050

24 1

653703019574