

#### Bi-Pin

Sunlite 03285-SU Q50/CL/GY6/120V Halogen 50-Watt Single Ended T3.5 Light Bulb, 120 Volt, GY6.35 (Bi-Pin) Base, Clear, 500 Lumen, 2000 Hour Life Span, 3200K - Warm White 2 Pack

Single Ended T3.5

### **DESCRIPTION:**

Sunlite Halogen Bulbs put out more lumens per watt (LPW) than standard incandescent bulbs. These 50-watt, 120-volt lamps feature a GY6.35 bi-pin base. Perfect for both indoor and outdoor applications. Use in chandeliers, track lighting, pendants, portable lamps, wall sconces, showcase displays, and more.

## FEATURES:

- HALOGEN LAMPS These UV protected 50-watt 120-volt halogen bulbs produce more lumens per watt (LPW) than standard incandescent bulbs.
- GY6.35 BASE These clear lamps feature a GY6.35 (bipin) base that works with a variety of applications. Each bulb measures 0.509 inches in diameter and 1.65 inches in overall height.
- DIMMABLE Fully dimmable when installed in a fixture with dimming control. Bright white, 500 lumen output.
- LONG LIFE With a 2000 hour life span these bulbs will last 1.8 years (based on 3 hours per day use).
- INDOOR AND OUTDOOR USE These bulbs are perfect for both indoor and outdoor applications. Use in chandeliers, track lighting, pendants, portable lamps, wall sconces, showcase displays, and more.



# sunlite

#### **General Characteristics**

## **Product Dimension**

Bulb Shape	Bi-Pin	MOL (in)	1.64
Average Rated Hours	2000	Diameter (in)	0.509"
Finish	Clear	Item Dimension (in)	(W) 0.51 (H) 1.64 (D) 0.51
Base	2-Pin Glass (GY6.35)	Package Dimension (in)	(W) 0.5 (H) 3.5 (D) 3.13
Average Life Span Years	2	Package Weight (lb)	0.020

#### **Electrical Characteristics**

Watts	50
Volts	120

# Light Characteristics

Lumens Brightness	500
Color Rendering Index CRI	100
Coating	UV Protected
Emitted Color	Bright White
Color Temperature Kelvin	3200K

## Additional Features

Title 20	Lawful for sa
Mercury Free	Yes

ale in California

ns	
	1.64
	0.509"

# **Product Data**

Case Unit Rate	6
Pack Size	2
Item UPC	653703032856
Package Type	Card