

ED Series

Sunlite 03645-SU MH100/U/MED M90 Metal Halide Lamp, 100 Watts, Pulse Start, Medium Base (E26), ED17, 12,000 Hours Life, 9000 Lumen, Clear Finish, 4000K

Metal Halide

DESCRIPTION:

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 100 watt metal halide bulbs have a bright 9000 lumen output. They are medium base (E26), ED17 bulbs with an average life span of 12,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. ANSI Code M90. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 2.18 inches in diameter, 5.36 inches tall.

FEATURES:

- **METAL HALIDE** - Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- **HIGH INTENSITY DISCHARGE** - This 100 watt bulb puts out a bright 9000 lumens of light. Color temperature is 4000K. Clear glass bulb.
- **MEDIUM BASE** - Standard medium base (E26) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 2.18 inches diameter, 5.36 inches tall.
- **PULSE START** - These bulbs feature pulse start for quicker startup, less lumen depreciation, long 12,000 hour average lifespan, and more lumens per watt so you save energy.
- **ANSI CODE M90** - This metal halide bulb is for use in M90 ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.



SPECIFICATIONS:

General Characteristics

| | |
|--------------------------------|--------------------|
| Bulb Shape | ED17 |
| Ansi code | M90 |
| Average Rated Hours | 12000 |
| Finish | Clear |
| Base | Medium Screw (E26) |
| Average Life Span Years | 11 |

Electrical Characteristics

| | |
|--------------|-----|
| Watts | 100 |
|--------------|-----|

Light Characteristics

| | |
|----------------------------------|------------|
| Lumens Brightness | 9000 |
| Color Rendering Index CRI | 65 |
| Coating | Uncoated |
| Emitted Color | Cool White |
| Color Temperature Kelvin | 4000K |
| Mercury Content | 10-13mg |

Product Dimensions

| | |
|-------------------------------|----------------------------|
| MOL (in) | 5.358 |
| Diameter (in) | 2.184" |
| Item Dimension (in) | (W) 2.18 (H) 5.36 (D) 2.18 |
| Package Dimension (in) | (W) 2.4 (H) 6 (D) 2.4 |
| Package Weight (lb) | 0.200 |

Product Data

| | |
|-----------------------|--------------|
| Case Unit Rate | 12 |
| Pack Size | 1 |
| Item UPC | 653703036458 |
| Warranty Years | 1 |