

ED Series

Sunlite 03646-SU MP150/C/U/MED M90/O Protected Metal Halide Lamp, 100 Watts, Medium Base (E26), Pulse Start, ED17, 15,000 Hours Life, 8500 Lumen, Clear Finish, 4000K

Protected Metal Halide

DESCRIPTION:

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. Energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 100 watt protected pulse start metal halide bulbs have a bright 8500 lumen output. They are medium base (E26), ED17 bulbs with an average life span of 15,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, wall packs, and other commercial and industrial lighting applications. ANSI Code M90/O. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 2.127 inches in diameter, 5.258 inches tall.

FEATURES:

- **PROTECTED METAL HALIDE** - Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- **HIGH INTENSITY DISCHARGE** - This 100 watt bulb puts out a bright 8500 lumens of light. Color temperature is 4000K. Clear glass bulb.
- **MEDIUM BASE** - Larger medium base (E26) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 2.127 inches diameter, 5.258 inches tall.
- **PULSE START** - These protected pulse start bulbs feature a long 15,000 hour average lifespan.
- **ANSI CODE M90/O** - This metal halide bulb is for use in M90/O ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.



SPECIFICATIONS:

General Characteristics

Bulb Shape	ED17
Ansi code	M90/O
Average Rated Hours	15000
Finish	Clear
Base	Medium Screw (E26)
Average Life Span Years	14

Electrical Characteristics

Watts	100
-------	-----

Light Characteristics

Lumens Brightness	8500
Color Rendering Index CRI	65
Coating	Uncoated
Emitted Color	Cool White
Color Temperature Kelvin	4000K

Product Dimensions

MOL (in)	5.258
Light Center Length	3.375"
Diameter (in)	2.127"
Item Dimension (in)	(W) 2.13 (H) 5.26 (D) 2.13
Package Dimension (in)	(W) 2.3 (H) 6 (D) 2.3
Package Weight (lb)	0.250

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703036465
Warranty Years	1

VARIATIONS:



03646-SU



03651-SU



03659-SU



03664-SU



03638-SU



03641-SU

Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
03646-SU	MP100/U/MED/PS	100	8500	65	4000K CW	15000	1
03651-SU	MP150/U/MED	150	13300	65	4000K CW	15000	1
03659-SU	MP250/U/PS	250	23800	65	4000K CW	15000	1
03664-SU	MP400/U/PS	400	33000	65	4000K CW	15000	1
03638-SU	MP50/U/MED/PS	50	3200	65	4000K CW	10000	1
03641-SU	MP70/U/MED	70	5600	65	4000K CW	15000	1