

ED Series

Sunlite 03659-SU MP50/C/U/MED M153/O
Protected Metal Halide Lamp, 250 Watts,
Mogul Base (E39), ED28, Pulse Start,
15,000 Hours Life, 23800 Lumen, Clear
Finish, 4000K
 Protected Metal Halide

DESCRIPTION:

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. Energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 250 watt protected pulse start metal halide bulbs have a bright 23800 lumen output. They are mogul base (E39), ED28 bulbs with an average life span of 15,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, wall packs, and other commercial and industrial lighting applications. ANSI Code M153/O. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 3.556 inches in diameter, 8.374 inches tall.

FEATURES:

- **PROTECTED METAL HALIDE** - Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- **HIGH INTENSITY DISCHARGE** - This 250 watt bulb puts out a bright 23800 lumens of light. Color temperature is 4000K. Clear glass bulb.
- **MOGUL BASE** - Larger mogul base (E39) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 3.556 inches diameter, 8.374 inches tall.
- **PULSE START** - These protected pulse start bulbs feature a long 15,000 hour average lifespan.
- **ANSI CODE M153/O** - This metal halide bulb is for use in M153/O ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.



SPECIFICATIONS:

General Characteristics

Bulb Shape	ED28
Ansi code	M153/O
Average Rated Hours	15000
Finish	Clear
Base	Mogul Screw (E39)
Average Life Span Years	14
Material	GLASS

Electrical Characteristics

Watts	250
--------------	-----

Light Characteristics

Lumens Brightness	23800
Mean Lumens	19000
Color Rendering Index CRI	65
Coating	Uncoated
Emitted Color	Cool White
Color Temperature Kelvin	4000K

Product Dimensions

MOL (in)	8.374
Diameter (in)	3.556"
Item Dimension (in)	(W) 3.56 (H) 8.37 (D) 3.56
Package Dimension (in)	(W) 3.9 (H) 9.4 (D) 3.9
Package Weight (lb)	0.550

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703036595
Warranty Years	1

VARIATIONS:



03659-SU



03646-SU



03651-SU



03664-SU



03638-SU



03641-SU

Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
03659-SU	MP250/U/PS	250	23800	65	4000K CW	15000	1
03646-SU	MP100/U/MED/PS	100	8500	65	4000K CW	15000	1
03651-SU	MP150/U/MED	150	13300	65	4000K CW	15000	1
03664-SU	MP400/U/PS	400	33000	65	4000K CW	15000	1
03638-SU	MP50/U/MED/PS	50	3200	65	4000K CW	10000	1
03641-SU	MP70/U/MED	70	5600	65	4000K CW	15000	1