

Bi-Pin**Sunlite 22005-SU Q35/GY8/120V Halogen
35-Watt Single Ended T3.5 Light Bulb,
300 Lumen, 120 Volt, GY8 (Bi-Pin) Base,
Clear, 2000 Hour Life Span, 1 Pack 3200K
- Warm White**

Single Ended T3.5

DESCRIPTION:

Sunlite Halogen Bulbs put out more lumens per watt (LPW) than standard incandescent bulbs. These 35-watt, 120-volt lamps feature a GY8 bi-pin base. Perfect for both indoor and outdoor applications. Use in chandeliers, track lighting, pendants, portable lamps, wall sconces, showcase displays, and more.

FEATURES:

- **HALOGEN LAMPS** - These UV protected 35-watt 120-volt halogen bulbs produce more lumens per watt (LPW) than standard incandescent bulbs.
- **GY8 BASE** - These clear lamps feature a GY8 (2-pin) base that works with a variety of applications. Each bulb measures 0.556 inches in diameter and 1.72 inches in overall height.
- **DIMMABLE** - Fully dimmable when installed in a fixture with dimming control. Bright white, 300 lumen output.
- **LONG LIFE** - With a 2000 hour life span these bulbs will last 1.8 years (based on 3 hours per day use).
- **INDOOR AND OUTDOOR USE** - These bulbs are perfect for both indoor and outdoor applications. Use in chandeliers, track lighting, pendants, portable lamps, wall sconces, showcase displays, and more.



SPECIFICATIONS:

General Characteristics

Bulb Shape	Bi-Pin
Average Rated Hours	2000
Finish	Clear
Base	2-Pin All Glass (GY8)
Average Life Span Years	2

Electrical Characteristics

Watts	35
Volts	120

Light Characteristics

Lumens Brightness	300
Color Rendering Index CRI	100
Coating	UV Protected
Emitted Color	Bright White
Color Temperature Kelvin	3200K

Additional Features

Title 20	Lawful for sale in California
Mercury Free	Yes

Product Dimensions


MOL (in)	1.72
Diameter (in)	0.556"
Item Dimension (in)	(W) 0.56 (H) 1.72 (D) 0.56
Package Dimension (in)	(W) 0.88 (H) 2.75 (D) 0.88
Package Weight (lb)	0.020

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703220055



VARIATIONS:



Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
22005-SU	Q35/GY8/120V	35	300	100	3200K BW	2000	1
22015-SU	Q100/GY8/120V	100	1500	100	3200K BW	2000	1
21995-SU	Q20/GY8/120V	20	120	100	3200K BW	2000	1
22010-SU	Q50/GY8/120V	50	500	100	3200K BW	2000	1