

**ST Series****Sunlite F25T8/SP735 25-Watt T8 Linear  
Fluorescent Light Bulb Medium Bi Pin  
Base, 3500K, 30-Pack**

T8 High Performance Straight Tube

**DESCRIPTION:**

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescents lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Performance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30140-SU F25T8/SP735 3500K Color Temperature T8 High Performance Straight Tube Fluorescent 25-Watt lamp features a Medium Bi Pin base, provides a light output of 2150 lumens at a Color Rendering Index (CRI) of 73 and can last an average of 20000 hours.

**FEATURES:**

- 25-Watt
- 3500K Color Temperature
- 20,000 hour average lamp life
- F25T8/SP735
- 2150 Lumens, 73 CRI



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	T8
<b>Average Rated Hours</b>	20000
<b>Base</b>	Medium 2-Pin (G13)
<b>Average Life Span Years</b>	18

### Electrical Characteristics

<b>Watts</b>	25
--------------	----

### Light Characteristics

<b>Lumens Brightness</b>	2150
<b>Color Rendering Index CRI</b>	73
<b>Emitted Color</b>	Neutral White
<b>Color Temperature Kelvin</b>	3500K

### Additional Features

<b>Rohs Compliant</b>	Yes
-----------------------	-----

### Product Dimensions

<b>MOL (in)</b>	36
<b>Diameter (in)</b>	1"
<b>Item Dimension (in)</b>	(W) 1 (H) 1 (D) 36
<b>Package Dimension (in)</b>	(W) 1.05 (H) 1.05 (D) 35.75
<b>Package Weight (lb)</b>	0.290

### Product Data

<b>Case Unit Rate</b>	30
<b>Pack Size</b>	1
<b>Item UPC</b>	653703301402

VARIATIONS:



Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
30140-SU	F25T8/SP735	25	2150	73	3500K NW	20000	1
30130-SU	F25T8/SP730	25	2150	73	3000K WW	20000	1
30151-SU	F25T8/SP750	25	2150	73	5000K SW	20000	1