

### **ST Series**

## Sunlite F39T5/841/HO 39-Watt T5 Linear Fluorescent Light Bulb Mini Bi Pin Base, 4100K, 40-Pack

T5 High Output High Performance Straight Tube

### DESCRIPTION:

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescents lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Perfomance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30425-SU F39T5/841/HO 4100K Color Temperature T5 High Output Hight Performance Straight Tube Fluorescent 39 Watt lamp features a Mini Bi Pin base, provides a light output of 3100 lumens at a Color Rendering Index (CRI) of 82 and can last an average of 20000 hours.

### FEATURES:

- The package length is 101.6 centimeters
- The package height is 14.478 centimeters
- The package width is 26.67 centimeters
- Package Weight : 9.3 pounds
- -



# sunlite

### **SPECIFICATIONS:**

### **Product Dimensions**

| Bulb Shape                 | T5                    | Size                   | 34" Inch                 |
|----------------------------|-----------------------|------------------------|--------------------------|
| Average Rated Hours        | 20000                 | MOL (in)               | 34.00                    |
| Base                       | Miniature Bi-Pin (G5) | Diameter (in)          | 0.625"                   |
| Average Life Span Years    | 18                    | Item Dimension (in)    | (W) 0.63 (H) 0.63 (D) 34 |
|                            |                       | Package Dimension (in) | (W) 0.64 (H) 0.64 (D) 34 |
| Electrical Characteristics |                       | Package Weight (lb)    | 0.24                     |
| Watts                      | 39                    |                        |                          |
|                            |                       | Product Data           |                          |
| Light Characteristics      |                       | Case Unit Rate         | 40                       |
| Lumens Brightness          | 3100                  | Pack Size              | 1                        |
| Color Rendering Index CRI  | 82                    | Item UPC               | 653703304250             |
| Emitted Color              | Cool White            |                        |                          |
| Color Temperature Kelvin   | 4100K                 |                        |                          |
| Color Temperature Kelvin   | 4100K                 |                        |                          |

#### **Additional Features**

Rohs Compliant

Yes

