

## A Series

### Sunlite 70321 LED A21 Emergency Rechargeable Battery Operated Light Bulb for Power Outage, 9 Watts (60w Equivalent), 800 Lumens, Medium E26 Base, Battery Backup, Non-Dimmable, 3000K Warm White 1 ct

Emergency bulb

#### DESCRIPTION:

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

#### FEATURES:

- **EMERGENCY LIGHT BULBS** - These emergency 9 Watt A21 LED bulbs have a medium (E26) base. You can use them as a regular light bulb (while its in use its getting charged) and when there is a power outage the bulb will stay lit for up to 4 hours at 400 lumens. Includes one socket cap hanging hook for use as a portable battery operated light source.
- **SAVE ENERGY** - Get the same light output of a 60 watt incandescent bulb while saving on electricity. The annual energy cost is a low \$1.08 (Based on 3 hours/day at \$0. 11 per/kWh) up to four hours of backup power
- **WARM WHITE** - At 3000K, these warm white bulbs provide a bright white light in bedrooms, living spaces, or anywhere you want to set a relaxed mood. 80 CRI
- **USES** - These LED emergency light bulbs are a perfect replacement for candles, emergency flashlights, and lanterns. This bulb can be used as a portable bulb, for camping, as a reading light, warehouse light, during a blackout, and hurricane season.
- **THE SAFER CHOICE** - These bulbs are a safe tool during a blackout. They are UL Listed for Damp Location installation. Ideal for both residential and commercial use. These bulbs contain no mercury or other harmful chemicals



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	A21
<b>Average Rated Hours</b>	25000
<b>Finish</b>	White
<b>Base</b>	Medium Screw (E26)
<b>Average Life Span Years</b>	23
<b>Ingress Protection</b>	IP20 (12.5 mm solids, Not protected from liquids)
<b>Dimmable</b>	No
<b>Material</b>	PC & Aluminum

### Electrical Characteristics

<b>Watts</b>	9
<b>Volts</b>	120
<b>Equivalent Wattage</b>	60
<b>LED Chip Manufacturer</b>	2835
<b>Power Factor</b>	0.9
<b>Temperature</b>	-4°F - 113°F

### Light Characteristics

<b>Lumens Brightness</b>	800
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	Warm White
<b>Color Temperature Kelvin</b>	3000K
<b>Beam Angle</b>	220°
<b>Flicker</b>	<30%

### Additional Features

<b>Safety Rating Mark</b>	UL Listed - Damp Location
---------------------------	---------------------------

### Product Dimensions

<b>MOL (in)</b>	2.76
<b>Diameter (in)</b>	5.31
<b>Item Dimension (in)</b>	(W) 2 (H) 5 (D) 2
<b>Package Dimension (in)</b>	(W) 2.75 (H) 5.5 (D) 2.75
<b>Package Weight (lb)</b>	0.29

### Product Data

<b>Case Unit Rate</b>	6
<b>Pack Size</b>	1
<b>Item UPC</b>	653703703213
<b>Warranty Years</b>	3
<b>Package Type</b>	Box

