

Plug-In

Sunlite LED PLL Recessed Plug & Play Long Twin Light Bulb, 17 Watt (FT40DL/40W BIAX Replacement) 2350 Lumens, 2G11 4-Pin Base Light-Tube, UL Listed, ROHS Compliant, 3000K Warm White, 1 Count

Plug and Play

### **DESCRIPTION:**

Upgrade your fluorescent bulbs with energy-efficient LED plug and play light bulbs, a direct replacement with no ballast bypass required. They are instant on at full brightness with no buzzing or flickering. With a life span of up to 50,000 hours, you will be required to replace difficult-to-reach bulbs less often. You will save maintenance costs and save energy at the same time. Our PLL bulbs feature a 2G11 4-Pin base and can be used for both commercial/residential locations. Please shop with confidence as these led bulbs are UL Listed and have been tested to meet their rigorous safety standards. They are also ROHS Certified. Unlike fluorescent bulbs, they contain no harmful chemicals and do not require special handling or disposal.

#### **FEATURES:**

- UPGRADE TO LED Replace your inefficient fluorescent bulbs with energy saving LED bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. Can be used in enclosed fixtures and has a High Color Rendering Index rating of 82.
- PLUG AND PLAY These Sunlite led bulbs replace inefficient fluorescent light bulbs with no bypass required. For use with electronic ballasts only. You can find a list of tested compatible ballasts included in the description in this listing.
- ENERGY EFFICIENT With a 3000K warm white color temperature each bulb Produces 2350 lumens of light while only using 17 watts of electricity! Annual energy costs are a low \$2.05 (Based on 3 hours/day at \$0.11/kWh).
- UL LISTED AND ROHS COMPLIANT These Sunlite bulbs are UL Listed and have been tested to meet their rigorous safety standards. They are also ROHS Certified unlike fluorescent bulbs, they contain no harmful chemicals and do not require special handling or disposal.
- MULTI USE With a lifespan of up to 50,000 hours our LED PLL Bulbs will retrofit into your existing troffers Ceiling Lights. Dimensions: 22.17" H x .67" D.



# SPECIFICATIONS:

## **General Characteristics**

Bulb Shape FT
Average Rated Hours 50000
Finish White
Base 4-Pin (2G11)
Average Life Span Years 46
Dimmable No
Material Glass

## **Electrical Characteristics**

 Amps
 0.142

 Watts
 17

 Equivalent Wattage
 40

 LED Chip Manufacturer
 2835

 Power Factor
 0.9

 Temperature
 -4°F - 113°F

#### **Light Characteristics**

Lumens Brightness2350Color Rendering Index CRI82Emitted ColorWarm WhiteColor Temperature Kelvin3000KBeam Angle140°

## **Additional Features**

Safety Rating Mark

DLC

PLC Number

DLC Classification

UL Listed - Damp Location

Yes

DDDKOK

Standard

# **Product Dimensions**

 MOL (in)
 22.48

 Diameter (in)
 0.69

 Item Dimension (in)
 (W) 1.8 (H) 1.4 (D) 22.6

 Package Dimension (in)
 (W) 2 (H) 1.5 (D) 23

 Package Weight (lb)
 0.95

#### **Product Data**

 Case Unit Rate
 10

 Pack Size
 1

 Item UPC
 653703810614

 Warranty Years
 5

 Package Type
 Box