

T Series

Sunlite 81260 LED T42 Bright High Lumen Bullet Corn Light Bulb, 60 Watts (450W Equivalent) 7200 lm, Medium Base (E26), 120-277 Volts, Non Dimmable, UL Listed Wet Location, 3000K Warm White, 1 Pack

High Lumen Lamps

DESCRIPTION:

Sunlite Bullet LED T42 bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness. Each bulb gives off a bright 7200 lumen output at 3000K warm white color temperature. Provides as much light as a 450 watt bulb while only using 60 watts of electricity. With a 50000 hour lifespan these bulbs will yield significant savings in electricity over their lifetime and require less maintenance for hard to reach bulbs. The 220 degree beam spread gives you a broader coverage of light than UFO bulbs and provides more downlight than corn bulbs. These bulbs are UL Listed for wet Location installation and are suitable for use in enclosed fixtures. Featuring Medium base (E26). For use in 120–277-volt fixtures. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications.

FEATURES:

- **UPGRADE TO LED** - These LED T42 bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness with no warmup time
- **ENERGY EFFICIENT** - These bulbs give out as much light as a 450 watt bulb while only using 60 watts of electricity. Estimated yearly energy cost is a low \$7.23. (Based on 3 hours/day use at \$0.11/kWh)
- **HIGH LUMEN OUTPUT** - Our LED T42 Bulbs provide a 220° beam spread giving them a broader spread than UFO bulbs and more downlight than corn bulbs. Each bulb gives off a bright 7200 lumens of light and has a color temperature of 3000K warm white
- **LONG LIFE** - With a 50000 hour lifespan these bulbs will provide significant savings in electricity over their lifetime and require less maintenance for hard to reach bulbs. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications
- **BALLAST BYPASS REQUIRED** - These LED bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions are included inside the packaging. It can also be found online or consult an electrician for more information



SPECIFICATIONS:

General Characteristics

Bulb Shape	T42
Average Rated Hours	50000
Finish	White
Base	Medium Screw (E26)
Average Life Span Years	46
Dimmable	No
Material	PC Cover & Aluminum

Electrical Characteristics

Watts	60
Volts	120-277
Equivalent Wattage	700
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-20-45°

Light Characteristics

Lumens Brightness	7200
Color Rendering Index CRI	80
Emitted Color	Warm White
Color Temperature Kelvin	3000K
Beam Angle	220°
Flicker	<30%

Additional Features

Safety Rating Mark	UL Listed - Wet Location
DLC	Yes
DLC Number	PLWG9IEA7WKS
DLC Classification	Standard

Product Dimensions

MOL (in)	10.97
Diameter (in)	5.51
Item Dimension (in)	(W) 5.32 (H) 9.9 (D) 5.32
Package Dimension (in)	(W) 5.8 (H) 10.5 (D) 5.8
Package Weight (lb)	2.3

Product Data

Case Unit Rate	6
Pack Size	1
Item UPC	653703812601
Warranty Years	3
Package Type	Box