

Sunlite 81295 LED Rectangle Up/Down Outdoor Wall Sconce Fixture, 12 Watts (120W=), Multi-Volt, 850 Lumens, Color Selectable 30K/40K/50K, 80 CRI, Dimmable, ETL Listed, for Commercial & Residential Use

Decorative

DESCRIPTION:

Sunlite's LED Rectangle Up/Down Outdoor Wall Sconce Fixture is an excellent choice to improve your outdoor lighting. Aluminum & steel construction and IP54 that can last years. These wall sconces have a long lifespan of 50,000 hours and are energy-efficient, using only 12W instead of traditional lighting options that require 120W to provide the same coverage. These fixtures allow you to choose the color temperature at the installation time. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight, depending on your preference, using a switch located on the back of the fixture. It can be dimmed when installed with an LEDcompatible dimmer. High color rendering at 80 CRI. ETL Listed for wet location installation. Hardware and instructions for mounting on any standard junction box included. Fixture measures 4.25 inches (W) x 9.16 inches (H) x 5.25 inches (D).

FEATURES:

- POLISHED DESIGN Its black finish and modern design are ideal for use on porches, walls, gardens or any outdoor space. Aluminum & steel construction and IP54 rated which are great protection from dust and other particles that will last for years.
- LONG LIFE SPAN These wall sconces have a long lifespan of 50,000 hours and are energy-efficient, using only 12W instead of traditional lighting options that require 120W to provide the same coverage.
- COLOR SELECTABLE These fixtures allow you to choose the color temperature at the installation time. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight, depending on your preference, using a switch located on the back of the fixture.
- DIMMABLE It can be dimmed when installed with an LED-compatible dimmer. High color rendering at 80 CRI.
- ETL LISTED ETL Listed for wet location installation. Hardware and instructions for mounting on any standard junction box included. Fixture measures 4.25 inches (W) x 9.16 inches (H) x 5.25 inches (D).



sunlite

SPECIFICATIONS:

General Characteristics

Average Life Span Years

Average Rated Hours

Finish

Dimmable Material

Lens Material

Lens Finish

-	Proa	ucu	CIIS	10
	14	D:	 :	<i>::</i>

Item Dimension (in)	(W) 4.25 (H) 9.16 (D) 5.25
Item Weight (Ib)	2.53
Package Dimension (in)	(W) 5.25 (H) 10.5 (D) 4.73
Package Weight (lb)	2.53

Product Data

Case Unit Rate Item UPC Warranty Years 6 653703812953 5

Electrical Characteristics				
Watts	6			
Volts	120-277			
Equivalent Wattage	2*60W Fluorescent			
LED Chip Manufacturer	СОВ			
Power Factor	0.9			
Temperature	<45			

50000

Black

Glass

clear

Aluminum & Steel

46 Yes

Light Characteristics

Lumens Brightness	850
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	30K/40K/50K
Beam Angle	120°
Flicker	>30%

Fixture Characteristics

Mounting	Wall
Fixture Technology	LED
Use Location	Outdoor

Additional Features

Safety Rating Mark Safety Rated For Canada Safety Rated For USA ETL Listed - Wet Location Yes Yes