

**Sunlite 85609 3.5" LED Three Head
Gimbal Regressed Downlight Fixture,
36W, 2270 Lmns, Canless, CCT Switch
27K/30K/35K/40K/50K, 90 CRI, Energy
Star, Dimmable, ETL Listed, Title-24
Compliant, 1 Pack**

DESCRIPTION:

Introducing Sunlite's Gimbal Downlight Fixture that is versatile and energy-efficient lighting solution for any space - featuring a gimbal design that allows for tilting the light head 15 degrees in either direction and rotating 360 degrees. The color selectable feature lets you choose between 2700K Soft White, 3000K Warm White, 3500K Neutral White, 4000K Cool White, or even 5000K Daylight depending on your preferences. These dimmable fixtures let you lower the brightness of your lights (10%-100%) Forward Phase (Triac or Incandescent) to fit any mood or décor. With a long 50,000-hour lifespan and Energy Star certification, these fixtures only use 36 watts of electricity with a high lumen output of 2270. Install them in entryways, living rooms, conference rooms, kitchens, and closets, and enjoy years of reliable and maintenance-free service with estimated annual energy costs of \$4.34 (Based on 3 Hrs/Day at \$0.11/kWh). The ETL listing makes them suitable for wet location installation, and the fixture dimensions are 3.25" H x 11.67" W x 4.37" D.

FEATURES:

- **THREE GIMBAL DESIGN** – Its gimbal design allows for tilting the light head 15 degrees in either direction and rotating 360 degrees, making it suitable for sloped ceilings and directional lighting. Each light features a 38-degree beam angle.
- **COLOR SELECTABLE** - These dimmable fixtures let you pick the color temperature using a switch on the fixture, you can choose between 2700K Soft White, 3000K Warm White, 3500K Neutral White, 4000K Cool White, or even 5000K Daylight depending on your preferences.
- **DIMMABLE & EASY TO INSTALL**- The seamless dimming feature allows you to lower the brightness of your lights (10%-100%) Forward Phase (Triac or Incandescent) to fit any mood or décor. High color rendering at 90 CRI. The fixture can be installed in a new construction or as a remodel without the need for any housing. The remote driver box connects to a 120-Volt power source.
- **ENERGY STAR** - With a long 50,000-hour life span, these will provide years of reliable and maintenance-free service that only uses 36 watts of electricity with a high lumen output of 2270. Estimated annual energy costs of \$4.34 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates.
- **ETL LISTED** - These are ETL Listed for wet location installation. Mounting hardware and installation instructions

SPECIFICATIONS:
General Characteristics

Bulb Shape	Square Trim
Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	Forward Phase (Triac or Incandescent)
Dimming Percentage	10-100%
Material	Metal
Lens Material	Polycarbonate
Lens Finish	Clear
Application	Residential

Electrical Characteristics

Watts	36
Volts	120
Equivalent Wattage	180
LED Chip Manufacturer	COB
Power Factor	0.9
Temperature	-4°F - 104°F

Light Characteristics

Lumens Brightness	2270
Color Rendering Index CRI	90
Emitted Color	CCT Selectable
Color Temperature Kelvin	27K/30K/35K/40K/50K
Beam Angle	38°

Fixture Characteristics

Style	Gimbal
Shape	Round
Number of Lights	3
Mounting	Recessed
IC Rating	Yes
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	ETL Listed - Wet Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
Mercury Free	Yes

Product Dimensions

Size	3.5"
MOL (in)	3.25"
Item Dimension (in)	(W) 11.67 (H) 3.25 (D) 4.37

Product Data

Case Unit Rate	6
Pack Size	1
Item UPC	653703856094
Warranty Years	5