

Sunlite 87709 LED 6-Inch Square Recessed Slim Downlight, 12 Watts (75W=), 950 Lumens, Color Selectable 27K/30K/35K/40K/50K, 90 CRI, Energy Star, ETL Listed, White, For Residential & Commercial Use

Slim

DESCRIPTION:

This 6-inch LED Recessed Slim Downlight from Sunlite features innovative technology that allows you to choose the color temperature at the time of installation. Selectable 27K/30K/35K/40K/50K color, depending on your preference. using a switch located on the back of the fixture. Its slim feature allows them to be installed in limited clearance areas. Use for new installations or as a replacement for existing recessed lighting. LED technology means 35,000 hours of maintenance-free service. No ladders to climb or difficult-toreach bulbs to replace. Comparable output to a 75-watt bulb while only using 12 watts of electricity. Estimated annual energy costs of \$1.45 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. Built-in long-life LED technology means 35,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace. This fixture is ETL Listed for Wet Location Installation. Good for commercial or residential installations. Suitable for entryways, bedrooms, kitchens, hallways, bathrooms, and more.

FEATURES:

- ULTRA SLIM DESIGN Shallow depth makes for easier installation, especially in low-clearance applications. No housing is required. Use these 6-Inch square fixtures for new facilities or as a replacement for existing recessed lighting.
- COLOR TEMPERATURE SELECTABLE This dimmable fixture put out a bright 950 lumen and allow you to choose the color temperature at the time of installation. Selectable 27K/30K/35K/40K/50K color, depending on your preference, using a switch located on the back of the fixture.
- DIMMABLE LED Fixture can be dimmed (100%-10%) when installed with an LED compatible dimmer. Output is a bright 950 lumens (75 watt equivalent) while only using 12 Watts of electricity. Instant on with no flickering or buzzing like fluorescent bulbs. High color rendering at 90 CRI.





35,000 hours of maintenance-free service. No ladders to





SPECIFICATIONS:

General Characteristics

Average Rated Hours Finish

Average Life Span Years

Dimmable Dimming Type

Dimming Percentage

Material
Lens Material
Lens Finish
Application

35000 White 32

Yes

Forward Phase (Triac or

Incandescent) 10-100%

Aluminum & PC
Polycarbonate

White Residential

Product Dimensions

Size
Item Dimension (in)
Package Dimension (in)
Package Weight (lb)
Cord Length

6" (W) 6.85 (H) 1.02 (D) 6.85 (W) 7.87 (H) 7 (D) 2.37 1.06 12"

Product Data

Case Unit Rate Pack Size Item UPC Warranty Years

1 653703877099 5

6

Electrical Characteristics

Watts12Volts120Equivalent Wattage75Power Factor0.9

Light Characteristics

Lumens Brightness 950
Color Rendering Index CRI 90

Emitted Color CCT Selectable

Color Temperature Kelvin 27K/30K/35K/40K/50K

Beam Angle 110° Flicker <30%

Fixture Characteristics

Shape Square Number of Lights 1

MountingRecessedIC RatingYesFixture TechnologyLEDUse LocationIndoor

Additional Features

Safety Rating Mark ETL Listed - Wet Location

Energy StarYesEnergy Star Number2397276Mercury FreeYes



ACCESSORIES:

Catalog # 50109-SU TRIM/SDL/6S/BN

Catalog # 50123-SU TRIM/SDL/6S/BK

Catalog # 88154-SU LED