

Sunlite 87805 LED 4-Inch Recessed Slim Downlight Fixture, 12 Watts (65W=), 700 Lumens, Indoor & Outdoor, Color Selectable 27K/30K/35K/40K/50K, 90 CRI, 120V, Dimmable, ETL Listed, Matte Black, 1 Pack

Slim

DESCRIPTION:

Sunlite's 4-inch Square Recessed Slim Downlight fixture features an ultra-slim design for a modern, minimalistic look that suits any interior style. This dimmable fixture puts out a bright 700 lumen and allows you to choose the color temperature at the time of installation. Tunable 27K/30K/35K/40K/50K color, depending on your preference, using a switch located within the junction box of the fixture. Comparable output to a 65-watt bulb while only using 12 watts of electricity. Estimated annual energy costs of \$1.45 (Based on 3 Hrs/Day at \$0.11/kWh). The fixture can be dimmed (100-10%) when installed with a Forward Phase (Triac or Incandescent) dimmer. High color rendering at 90 CRI. This fixture is ETL Listed for Wet Location Installation. Suitable for indoor and outdoor use. Ideal for entryways, bedrooms, kitchens, hallways, bathrooms, basements, soffits, porches, and more. Fixture Dimensions 1" H x 4.87" D.

FEATURES:

- COLOR SELECTABLE This dimmable fixture puts out a bright 700 lumen and allows you to choose the color temperature at the time of installation. Tunable 27K/30K/35K/40K/50K color, depending on your preference, using a switch located within the junction box of the fixture.
- EASY INSTALLATION The 4-inch square recessed slim downlight fixture ensures a modern, minimalistic look that complements any interior style. This fixture can be installed in new construction or as a remodel, without the need for additional housing. The remote driver box connects to a 120V line voltage power source. Mounting hardware and installation instructions included.
- LONG LIFE LED LED technology means 50,000 hours of maintenance-free service. No ladders to climb or difficultto-reach bulbs to replace. Comparable output to a 65-watt bulb while only using 12 watts of electricity. Estimated annual energy costs of \$1.45 (Based on 3 Hrs/Day at \$0.11/kWh).



mmed (100-10%) when ac or Incandescent) CRI enhances your tres accurate color

isted for Wet Location outdoor use. Ideal for 'lways, bathrooms,

basements, soffits, porches, and more. Fixture Dimensions



744 Clinton Street Brooklyn, NY, 11231 | 718.768.7000

sunlite

General Characteristics

Average Rated Hours Finish	50000 Black
Average Life Span Years	46
Dimmable	Yes
Dimming Type	Forward Phase (Triac or Incandescent)
Dimming Percentage	10-100%
Lens Material	Polycarbonate
Lens Finish	Frosted

Product Dimensions

4	"

Product Data

Size

Case Unit Rate	12
Item UPC	653703878058
Warranty Years	3

Electrical Characteristics

Watts	12
Volts	120
Power Factor	0.9
Temperature	-4°F~104°F

Light Characteristics

Lumens Brightness	800
Color Rendering Index CRI	90
Emitted Color	CCT Selectable
Color Temperature Kelvin	27K/30K/35K/40K/50K
Beam Angle	120°

Fixture Characteristics

Shape	Square
Number of Lights	1
Mounting	Recessed
IC Rating	Yes
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	ETL Listed - Wet Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
Mercury Free	Yes