

T Series

Hybrid Type A + B

DESCRIPTION:

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

FEATURES:

-
-
-
-
-



SPECIFICATIONS:

General Characteristics

Bulb Shape	Linear Tube
Average Rated Hours	50000
Finish	Frosted
Base	Medium 2-Pin (G13)
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Material	Glass

Electrical Characteristics

Amps	.076
Watts	8
Volts	120-277
Equivalent Wattage	F17T8, F24T8
LED Chip Manufacturer	SMD2835
Power Factor	>0.9
Temperature	-4°F - 113°F
Total Harmonic Distortion	<20%

Light Characteristics

Lumens Brightness	1100
Color Rendering Index CRI	83
Coating	PET Coating
Emitted Color	CCT Tunable
Color Temperature Kelvin	35K/40K/50K
Beam Angle	320°
Flicker	No

Additional Features

Safety Rating Mark	UL Listed - Damp Location
UL Rated Enclosed Fixtures	Yes
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Classification	Standard
Mercury Free	Yes

Product Dimensions

Size	2'
MOL (in)	23.19
Diameter (in)	1

Product Data

Case Unit Rate	25
Pack Size	1
Item UPC	653703880365
Warranty Years	5

