

ST Series

Sunlite 88090 F28T5/F32T8/F40T12 4-Foot LED T8 Plug & Play Light Bulb, 12 Watts, 1800 Lumens, 3000K Warm White, Medium (G13) 2-Pin Base, UL Listed, White, 1-Pack

Plug and Play

DESCRIPTION:

Sunlite's 4-Foot LED T8 Plug & Play Light Bulb is a highquality lighting solution designed to provide bright, energyefficient illumination in any setting. With up to 50,000 hours of reliable service, the 12-watt LED bulbs produce 1800 lumens of warm white light at 3000K, ideal for various applications. These innovative bulbs feature a G13 bi-pin base that secures and stable connection between your fixture and the bulb, ensuring a consistent flow of light without flickering or power loss. Moreover, the bulbs' glass construction ensures they won't yellow over time, and they are UL and DLC listed for maximum safety and efficiency. Dimensions 47.67" L x .98" D.

FEATURES:

- UPGRADE TO LED Replace your inefficient bulbs with energy saving LED bulbs from Sunlite. Long life LED technology means up to 50,000 hours of reliable service while only using 12 watts of electricity with a lumen of 1800, so you'll need replace difficult to access bulbs less often.
- PLUG AND PLAY These Sunlite led bulbs replace inefficient light bulbs with no bypass required. Moreover, the bulbs' glass construction ensures they won't yellow over time.
- G13 2-PIN BASE This provides a secure and stable connection between your fixture and the bulb, ensuring a consistent flow of light without flickering or power loss.
- WARM WHITE At 3000K these warm white light bulbs provide warm lighting for hallways, stairways, closets, bathrooms, vanities or anywhere you need an inviting atmosphere and bright light. High CRI (Color Rendering Index) of 82.
- UL & DLC LISTED These Sunlite bulbs are UL Listed for damp location and have been tested to meet their rigorous safety standards. DLC listed for maximum safety and efficiency. Dimensions 47.67" L x .98" D.



sunlite

SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours Finish Base Average Life Span Years Dimmable Material

Electrical Characteristics

Watts	12
Equivalent Wattage	F28T5, F32T8, F40T12
Temperature	-20° to 45°
Ballast Factor	Ballast Compatible

Τ8

46

No

Glass

1800

3000K

220°

Warm White

82

50000

White

Medium 2-Pin (G13)

Light Characteristics

Lumens Brightness Color Rendering Index CRI **Emitted Color** Color Temperature Kelvin **Beam Angle**

Additional Features

Safety Rating Mark UL Rated Enclosed Fixtures Yes Safety Rated For Canada Yes Yes Safety Rated For USA DLC Yes **DLC Number DLC Classification**

UL Listed - Damp Location PLY4R71RRWMM Standard

Product Dimensions

Size	
MOL (in)	
Diameter (in)	
Item Dimension (in)	
ltem Weight (lb)	
Package Dimension (in)	
Package Weight (lb)	

Product Data

Case Unit Rate Pack Size Item UPC Warranty Years Package Type

4 Foot 47.67 0.98 (W) 0.98 (H) 0.98 (D) 47.67 0.710 (W) 1 (H) 1 (D) 24 0.500

10 1 653703880907 5 Sleeve