

**Plug-In****Sunlite 88292-SU LED PLD Ballast  
Bypass Light Bulb, 9 Watts (26W  
Equivalent), G24d Base, CFL  
Replacement, UL Listed, 30K - Warm  
White 1 Pack**

Bypass

**DESCRIPTION:**

Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED ballast bypass bulbs from Sunlite. 270 degree beam angle that can be rotated at the base for optimal coverage. LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 950 lumen with Warm White color temperature at 3000K. Provides up to 50,000 hours of energy efficient light so you'll have to replace difficult to access bulbs less often. Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They are UL Listed for damp location installation. These 2-Pin base (G24d) bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs.

**FEATURES:**

- **UPGRADE TO LED** - Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED ballast bypass bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. They feature a 2-Pin base (G24d) and a 270 degree beam angle that can be rotated at the base for optimal coverage.
- **ENERGY EFFICIENT** - These 9 watt LED bulbs are direct replacements for 26 watt CFL bulb. Low annual operating costs of only \$1.08. (Based on 3 Hours/Day at \$0.11/kWh)
- **LONG LIFE SPAN** - Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Makes commercial and residential fixtures virtually maintenance-free.
- **A SAFER CHOICE** - Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They work with your existing ballasts so no special wiring or modifications are needed. They are UL Listed for damp location installation.
- **BALLAST BYPASS REQUIRED** - These fluorescent replacement LED bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions available online or consult an electrician for more information.



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	PLD
<b>Average Rated Hours</b>	50000
<b>Finish</b>	White
<b>Base</b>	2-Pin LED Base (G24d)
<b>Average Life Span Years</b>	46
<b>Dimmable</b>	No
<b>Material</b>	Aluminum & Plastic

### Electrical Characteristics

<b>Watts</b>	9
<b>Volts</b>	120-277
<b>Equivalent Wattage</b>	18
<b>LED Chip Manufacturer</b>	Epistar 2835
<b>Power Factor</b>	0.9
<b>Temperature</b>	-20° to 45°

### Light Characteristics

<b>Lumens Brightness</b>	950
<b>Color Rendering Index CRI</b>	82
<b>Emitted Color</b>	Warm White
<b>Color Temperature Kelvin</b>	3000K
<b>Beam Angle</b>	270°

### Additional Features

<b>Safety Rating Mark</b>	UL Classified - Damp Location
<b>UL Rated Enclosed Fixtures</b>	Yes

### Product Dimensions

<b>MOL (in)</b>	6.61
<b>Diameter (in)</b>	1.1
<b>Item Dimension (in)</b>	(W) 1.4 (H) 6.61 (D) 1.39
<b>Item Weight (lb)</b>	0.010
<b>Package Dimension (in)</b>	(W) 1.5 (H) 6.75 (D) 1.5
<b>Package Weight (lb)</b>	0.230

### Product Data

<b>Case Unit Rate</b>	12
<b>Pack Size</b>	1
<b>Item UPC</b>	653703882925
<b>Warranty Years</b>	5
<b>Package Type</b>	Box